



- NOTES:**
1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
 3. PIN SETBACK: 0.10" [2.5MM]
EN 60601 TOUCHPROOF
 4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
EXTRACTION FORCE: 3.7 LBS AVERAGE (16.5N)
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 11 AMPS
 5. OPERATING TEMPERATURE: +5°C TO +60°C
 6. UL94 V-0/5V
 7. DIN 802 COMPLIANT

REV	DESCRIPTION	DATE	BY
F	REV PER ECO 27944 KDS 10/11/16	10/18/16	SLW
E	REV PER ECO 26711 TAS 3/23/16	3/29/16	KE
	REDRAWN IN SOLIDWORKS XZ 10/14/15		
D	REV PER ECO 3390 GSOX 2/24/98	3/4/98	GSOX
C	REV PER ECO 2556 SJ 1/29/97	2/4/97	SJ
B	REV PER ECO 2187 RS 5/13/94	8/14/97	RS
A	RELEASE PER ECO 596 RS 4/26/94	5/13/94	LL
REVISIONS			

TOLERANCES	
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC	
FRACTIONAL	$\pm 1/64$
DECIMAL	.00 \pm .01 [.25mm] .000 \pm .005 [.127mm]
ANGULAR	$\pm .5^\circ$

APPROVALS	DATE
DRAWN SINCLAIR	10/27/93
CHECKED <i>X show</i>	10/12/16
PROJ ENGR SINCLAIR	10/27/93
APPROVED <i>R. Spady</i>	10/14/16
PROJECT 1302	FSCM

PlasticsOne
Medical, Research & Audio Components
6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018
PHONE: 540-772-7950 FAX: 540-989-7519

TITLE JACK, PANEL MOUNT, ϕ 1.5mm

SCALE 5:1

SIZE B	DWG 36145-50	REV F	SHT OF 1
------------------	-----------------	----------	-------------

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.