



- △ F NOTES:**
1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
 3. PIN SETBACK: 0.10" [2.5MM]
EN 60601 TOUCHPROOF
 4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
EXTRACTION FORCE: 3.7 LBS AVERAGE (16.5N)
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 11 AMPS
 5. OPERATING TEMPERATURE: +5°C TO +60°C
 6. UL94 V-0/5V
 7. DIN 802 COMPLIANT

REV	DESCRIPTION	DATE	APPVD
F	REV PER ECO 27944 KDS 10/11/16	10/18/16	SLW
E	REV PER ECO 26711 TAS 3/23/16	3/29/16	KE
	REDRAWN IN SOLIDWORKS XZ 10/14/15		
D	REV PER ECO 6198 JS 2/4/02	2/13/02	DMB
C	REV PER ECO 2556 SJ 1/29/97	2/4/97	SJ
B	REV PER ECO 1264 SJ 7/5/95	12/12/95	WON
A	REL PER ECO 596 RS 4/22/94	5/13/94	LL
REVISIONS			

TOLERANCES
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC
FRACTIONAL ±1/64
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]
ANGULAR ±.5°

APPROVALS	DATE
DRAWN SINCLAIR	10/27/93
CHECKED <i>[Signature]</i>	10/12/16
PROJ ENGR SINCLAIR	10/27/93
APPROVED <i>[Signature]</i>	10/14/16
PROJECT 1302	FSCM

PlasticsOne
 Medical, Research & Audio Components
 6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018
 PHONE: 540-772-7950 FAX: 540-989-7519

TITLE JACK, PANEL MOUNT, Ø1.5mm

SCALE 5/1

SIZE DWG B 36502-50

REV F SHT 1 OF 1

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.