



- NOTES:**
1. MATERIAL: PBT  
OTHER MATERIALS AVAILABLE
  2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
  3. PIN SETBACK: 0.10" [2.5MM]  
EN 60601 TOUCHPROOF
  4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)  
EXTRACTION FORCE: 3.7 LBS AVERAGE (16.5N)  
LIFE CYCLE: 1000+ INSERTION CYCLES  
MAX. CURRENT: 11 AMPS
  5. OPERATING TEMPERATURE: +5 °C TO +60 °C
  6. UL94 V-0/5V
  7. DIN 802 COMPLIANT

REV	DESCRIPTION	DATE	APPVD
F	REV PER ECO 27944 KDS 10/11/16	10/13/16	SLA
E	REV PER ECO 26711 TAS 3/23/16	3/29/16	KE
	REDRAWN IN SOLIDWORKS XZ 10/14/15		
D	REV PER ECO 3390 GSOX 2/24/98	3/4/98	GSOX
C	REV PER ECO 2556 SJ 1/29/97	2/4/97	SJ
B	REV PER ECO 1264 SJ 7/5/95	12/12/96	SJ
A	REL PER ECO 714 RS 6/9/94	6/22/94	RS

TOLERANCES  
UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS IN INCHES  
DIMENSIONS IN [ ] METRIC

FRACTIONAL  
±1/64

DECIMAL  
.00 ±.01 [.25mm]  
.000 ±.005 [.127mm]

ANGULAR  
±.5°

APPROVALS	DATE
DRAWN SINCLAIR	2/23/94
CHECKED <i>X</i>	10/12/16
PROJ ENGR SINCLAIR	2/23/94
APPROVED <i>K. Grady</i>	10/14/16
PROJECT 1302	FSCM

**PlasticsOne**  
Medical, Research & Audio Components  
6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018  
PHONE: 540-772-7950 FAX: 540-989-7519

TITLE JACK, PANEL MOUNT, Ø1.5mm

SCALE 5/1

SIZE B DWG 36671-50 REV F SHT 1 OF 1

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.