



SCALE: 2:1

- NOTES:**
1. MATERIAL: PBT  
OTHER MATERIALS AVAILABLE
  2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
  3. PIN SETBACK: 0.17" (4.4 mm)  
EN 60601 TOUCHPROOF
  4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)  
EXTRACTION FORCE: 3.0 LBS MINIMUM (13.3N)  
LIFE CYCLE: 1000+ INSERTION CYCLES  
MAX. CURRENT: 8 AMPS
  5. OPERATING TEMPERATURE: +5° C to +60° C
  6. UL94 V-0/5V
  7. WAVE SOLDERABLE
  8. MATES WITH 441 (881), 503, 455, 592
  9. DIN 42-802 TYPE BU

REV.	DESCRIPTION	DATE	APPROVED
E	REV PER ECO 31956 XZ 9/4/18	9/26/18	SJA
D	REV PER ECO 18929 XZ 10/15/12	10/18/12	XZ
C	REV PER ECO 10098 JAP 11/7/2006	3/26/2008	JAP
B	REV PER ECO 1268 SJ 7/5/95	12/12/95	WON
A	REL PER ECO 893 SJ 10/26/94	10/26/94	SJ
REVISIONS			

TOLERANCES	APPROVALS	DATE
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [ ] METRIC	DRAWN BRINDLE	9/14/94
FRACTIONAL ±1/64	CHECKED <i>T. Stump</i>	9/18/18
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]	PROJ ENGR	
ANGULAR ±5°	APPROVED <i>R. Spulley</i>	9/18/18
	PROJECT	FSCM

**PlasticsOne**<sup>®</sup>  
 Medical, Research & Audio Components  
 6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018  
 PHONE: 540-772-7950 FAX: 540-989-7519

TITLE JACK, 1.5mm TOUCH PROOF  
 PANEL MOUNT

SCALE 5/1

SIZE	DWG	REV	SHT
A	36880-50	E	1 OF 1

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.