



NOTES:

1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
3. PIN SETBACK: 0.10" [2.5MM]
EN 60601 TOUCHPROOF
4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
EXTRACTION FORCE: 3.7 LBS AVERAGE (16.5N)
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 11 AMPS
5. OPERATING TEMPERATURE: +5°C TO +60°C
6. UL94 V-0/5V
7. DIN 802 COMPLIANT

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.

TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC				APPROVALS	DATE	<h1>PlasticsOne</h1> <p>Medical, Research & Audio Components 6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018 PHONE: 540-772-7950 FAX: 540-989-7519</p>
D	REV PER ECO 27944 KDS 10/11/16	10/18/16	SLA	DRAWN SINCLAIR	9/16/97	
C	REV PER ECO 26711 T AS 3/23/16 REDRAWN IN SOLIDWORKS XZ 10/14/15	3/29/16	KE	CHECKED <i>[Signature]</i>	10/12/16	
B	REV PER ECO 3390 GSOX 2/24/98	3/4/98	GSOX	PROJ ENGR SINCLAIR	9/16/97	SIZE DWG B 37913-50 REV D SHT 1 OF 1
A	REL PER ECO 3109 RS 10/13/97	10/13/97	RS	APPROVED <i>[Signature]</i>	10/14/16	
REV	DESCRIPTION	DATE	APPVD	PROJECT 6942	FSCM	
REVISIONS						

D
C
B
A