



- △ NOTES:
1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
 3. PIN SETBACK: 0.10" [2.5MM]
EN 60601 TOUCHPROOF
 4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
EXTRACTION FORCE: 1.8 LBS AVERAGE (8.0N)
LIFE CYCLE: 1000+ INSERTION CYCLES
HIPOT: 1000 VAC BETWEEN CONTACTS
MAX. CURRENT: 8 AMPS
 5. OPERATING TEMPERATURE: +5°C TO 60°C
 6. UL94 V-0/5V
 7. WAVE SOLDERABLE

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.

REV.	DESCRIPTION	APPROVAL DATE	APPROVED BY
C	REV PER ECO 27895 TAS 10/7/16	10/18/16	SLA
B	REV PER ECO 17476 TAS 3/15/12	3/27/12	JED
A	REL. PER. ECO# 4269 GSDX 5/17/99	5/18/99	GSDX

TOLERANCES UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC	APPROVALS	DATE
FRACTIONAL ±1/64	DRAWN GSDX	5/10/99
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]	CHECKED GSDX	10/11/16
ANGULAR ±.5°	PROJ ENGR GSDX	5/10/99
	APPROVED K. Spauldy	10/14/16
	PROJECT 7107	FSCM

PlasticsOne®
 Medical, Research & Audio Components
 6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018
 PHONE: 540-772-7950 FAX: 540-989-7519

TITLE
 JACK, THREADED PANEL MOUNT, 1MM

SCALE 4:1

SIZE DWG
 B 38255-50

REV SHT 1
 C OF 1