



- NOTES:**
1. MATERIAL: PBT
OTHER MATERIALS AVAILABLE
 2. SIGNAL CONTACT PLATING: SOFT NICKEL, THEN SOFT GOLD
 3. PIN SETBACK: 0.23" (5.8 mm)
EN 60601 TOUCHPROOF
 4. GENERAL PERFORMANCE (CONTACT POI FOR TEST CONDITIONS)
EXTRACTION FORCE: 3.7 lbs (16.5 N) Average
LIFE CYCLE: 1000+ INSERTION CYCLES
MAX. CURRENT: 8 AMPS
 5. OPERATING TEMPERATURE: +5° C to + 60° C
 6. UL94 V-0/5V
 7. WAVE SOLDERABLE
 8. MATES WITH 255
 9. Max Flash .003"

REV	DESCRIPTION	DATE	BY
A	Release per ECO 32027 SLH	8/15/18	SLH

REVISIONS

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND MAY NOT BE ISSUED OR REPRODUCED, IN WHOLE, OR IN PART, WITHOUT THE EXPRESS WRITTEN PERMISSION OF PLASTICS ONE INC.

TOLERANCES		APPROVALS	DATE
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES DIMENSIONS IN [] METRIC		DRAWN S Heckman	6/16/18
FRACTIONAL ±1/64		CHECKED S. Bryan	11/1/18
DECIMAL .00 ±.01 [.25mm] .000 ±.005 [.127mm]		PROJ ENGR	
ANGULAR ±.5°		APPROVED JEO	11/1/18
		PROJECT	FSCM

PlasticsOne
 Medical, Research & Audio Components
 6591 MERRIMAN ROAD, S.W., ROANOKE, VA, 24018
 PHONE: 540-772-7950 FAX: 540-989-7519

TITLE
JACK FEMALE, 2MM, PANEL MOUNT

SCALE 1:1

SIZE	DWG	REV	SHT
A	43008-50	A	1 OF 1